Supporting Document 15

OPT-13-95 FRI 16:22 SEY-14-92 MON 14:28

#### Record of Decision Amendment Environmental Conservation and Chemical Corporation

#### LOCATION AND DESCRIPTION

AWD TECHNOLOGIES INC

AWD PECHNOLOGIES INDY

The Environmental Conservation and Chemical Corporation (also referred to as Enviro-Chem, or ECC) and the Northside Sanitary Landfill (NSL) facilities are both on the Superfund National Priorities List, and are located adjacent to each other. On September 25, 1987, a Record of Decision (ROD) was signed which selected a combined remedy for the two sites. Since the time the original ROD was signed, U. S. EPA and the State of Indiana have engaged in negotiations with Potentially Responsible Parties (PRPs) for each site. These negotiations have resulted in separate remedies for each site, individual Consent Decrees for each site, this amendment to the 1987 ROD, and an amendment to the 1987 ROD relating to the MSL site. The purpose of this ROD Amendment is to describe the changes from the remedy selected in the 1987 ROD, as they pertain to ECC. ...

The Maviro-Chem site is located in a rural area of Boone County, about five miles north of Mionswille and ten miles northwest of NEW Conspolis. Farmland borders the southern edge of the site and normers the eastern edge of MSL. Residential properties are located to the north and west, within one-half mile of the facility. A small residential community, Northfield, is located north of the site on U.S. 421. Approximately fifty residences are located within one mile of the site.

An unnamed ditch runs north to south between the ECC and NSL sites, along the western edge of MSL, and joins Finley Creek at the southwestern corner of the MSL landfill. Finley Creek runs along the eastern and southern edges of the MSL site and flows into Eagle Creek about one-half mile downstream from the sites. Eagle Creek flows south from its confluence with Finley Creek for ten miles before it empties into Eagle Creek Reservoir. The reservoir supplies approximately six percent of the drinking water for the City of Indianapolis.

#### II, SITE HISTORY AND ENFORCEMENT ACTIVITIES

The 1987 ROD set forth the history of the ECC site through the date of its issuance. Subsequent to the issuance of the 1987 ROD, the following activities of pertinence have occurred:

1. Both before and after the 1987 ROD was issued, a group of defendants, who in 1983 had entered into a partial settlement of a pending court action, proposed to clean up the Enviro-Chem site utilizing a soil vapor extraction system. In a letter dated

| Fax #             |      | Fax # 700 LAG XX77    |  |
|-------------------|------|-----------------------|--|
| Phone #           |      | Phone #               |  |
| Co./Dept.         |      | Co.                   |  |
| TO NWB            |      | From M. DOWIAK        |  |
| Post-it* Fax Note | 7671 | Date 10/13 pages > /2 |  |

Yebruary 1988, EPA rejected this proposal because, among other deficiencies, the proposal failed to consider the cost of pilot testing or of a granular activated carbon system to treat the extracted vapor.

- 2. Subsequently, this group of defendants undertook a pilot soil vapor extraction study at Enviro-Chem. The results of the study, which was performed in June 1988, indicate that a vapor extraction system, with certain enhancements, may significantly reduce the levels of volatile organics and phenois in the soils.
- 3. These same parties then offered to perform a remedy at the Enviro-Chem site utilizing a closed soil vapor extraction system, with a granulated activated carbon system to treat the extracted vapor. In response, U.S. EPA and the State of Indiana entered into negotiations with these perties concerning the terms under which they might assume responsibility for remediating the site. The proposed Consent Decree and Exhibit A, which were placed in the Administrative Record, embody these negotiated terms and provide the details of the remedy as it will be performed pursuant to the ROD as amended, herein.

#### III. COMMUNITY RELATIONS

This ROD amendment, as proposed, was available for public comment for a thirty day period, pursuant to Section 117 of BARA. An Administrative Record containing the documents considered or relied upon in reaching the decision in this Amendment has been available at the Bionsville Town Hall and at the offices of Region V, U.S. EPA. in Chicago.

## IV. DOCUMENTATION OF SIGNIFICANT CHANGES FROM 1987 ROD

This ROD Amendment addresses those elements of the remedy which have changed from the 1987 ROD and the requirements and preferences under SARA. Many elements of the original 1987 ROD do not change. Therefore, the findings made in the 1987 ROD remain the same except for the changes described in this ROD Amendment.

The major differences between the remedy selected for ECC in the 1987 ROD and the remedy selected in this amendment are as follows:

- The use of soil vapor extraction technology is selected in this Amendment, instead of the ground water collection and ensite treatment selected in the 1987 ROD.
- The ground water collection and treatment selected in the 1987 ROD would have resulted in cleanup of the site after a long period of system operation, whereas the soil Vapor extraction selected in this Amendment will result

in cleanup of the site in a significantly shorter period of time.

- There were no on-site cleanup criteria specified in the 1987 ROD; this Amendment specifies Acceptable Soil Concentrations, which are based on ingestion of subsurface water at the site boundary and Acceptable Subsurface Water concentrations based on 1x10-6 risk, on Maximum Contaminant Levels, on Maximum Contaminant Level Proposed Goals, or on Lifetime Drinking Water Health Advisories.
- If the soil vapor extraction does not reduce the specified onsite contaminants to their cleanup standards within 5 years, a subsurface water collection system may be installed, the collected water treated in accordance with Clean Water Act and CERCLA requirements, and disposed of. This contingent activity is similar to a major component of the 1987 ROD remedy, which required collection and onsite treatment of ground water. However, under this ROD Amendment, the interception of the ground water will occur at a point nearer the ECC contamination.

Key portions of the remedy which remain the same from 1987 to 1989 are summarized here:

of the site.

- Access restrictions will be implemented to control use
- A RCRA Subtitle C cap will be installed to prevent direct contact with contaminated soils, and to reduce infiltration. The cap will also enhance the vapor recovery component of the amended remedy.
- The off-site cleanup levels (Acceptable Stream Concentrations) remain the same as in the 1987 ROD, except that a cleanup criterion for PCBs has been added, which represents a 1x10-6 risk level.
- Monitoring of the subsurface water and surface water will be implemented to ensure that no contamination reaches the Unnamed Ditch and Finley Creek.

This ROD Amendment selects separate and distinct remedies for ECC and NSL. During the design phase for each remedy, however, efforts will be made to ensure that the two remedies will be compatible with each other.

P. 06

5

#### SUMMARY

#### ENVIRONMENTAL CONSERVATION AND CHEMICAL CORPORATION DIFFERENCES BETWEEN 1987 REMEDY AND REMEDY, AS MODIFIED

#### 1987 REMEDY MODIFIED REMKDY Combined remedy for ECC and MSL Saparate, compatible remedies for ECC and NSL Ground water collection and Soil vapor extraction treatment Long-term treatment of ground Removal of source of contamination by water reducing concentra-tions of organic chemicals to cleanup levels within 5 Years No on-site cleanup criteria Acceptable Soil Con-· centrations and Accaptable Subsurface Water Concentrations established No additional remedial Subsurface water col-

requirements if cleanup standards not achieved

lection and treatment instituted if soil vapor extraction does not achieve cleanup levels in 5 years

Figure 1 shows some components of the remedial action selected in this ROD Amendment.

#### V. DESCRIPTION OF MODIFIED REMEDY

The technical attachment to the Consent Decree (Exhibit A) provides details regarding the remedial action selected in this ROD Amendment. The remedial action consists of the following general components:

- Soil vapor extraction, concentration and destruction
- RCRA Subtitle C cap Access restrictions
- Subsurface and Surface Water Monitoring
- Contingent subsurface water collection and treatment

б

#### Soil Vapor Extraction. Concentration and Destruction

The objective of the soil vapor extraction activity is to remove and destroy volatile organic compounds and selected base neutral/acid organics from the soils through a series of injection and extraction trenches. Operation of the soil vapor extraction system will be terminated when the Acceptable Soil Concentrations, as shown in Attachment 1, and discussed below, are achieved and verified as specified below.

The 1987 ROD selected Acceptable Stream Concentrations as ARARS for off-site subsurface vater and for surface vater. In addition, a cleanup level for PCBs has been added, which represents a 1x10-6 risk level. Achievement of the Acceptable Stream Concentrations for off-site subsurface water and surface water are also required in this ROD Amendment.

Because this ROD Amendment adds a source removal component, additional standards and regulations are applicable or relevant and appropriate. To confirm that the required level of cleanup of on-site soils has occurred, this ROD Amendment establishes Acceptable Subsurface Water Concentrations which must be met in on-site till wells, and Acceptable Stream Concentrations which must be met in off-site subsurface water and surface water.

Those Acceptable Subsurface Water Concentrations specified herein are either risk-based standards, Maximum Contaminant Levels, Maximum Contaminant Levels, Maximum Contaminant Level Proposed Goals or Lifetime drinking Water health advisories. The Acceptable Subsurface Water Concentrations specified in Attachment 1 will have to be met in on-site till wells as part of the post soil cleanup verification required to shut off the soil vapor extraction system. In addition, these cleanup levels form the basis for the Acceptable Soil Concentrations.

The Acceptable Soil Concentrations will have to be met in on-site soil samples as part of the post soil cleanup verification required to shut off the soil vapor extraction system. They are based on ingestion of subsurface water at the site boundary, and are calculated from the Acceptable Subsurface Water Concentrations, assuming a dilution of leachate to subsurface water of 1:196, and using established partition coefficients. The ratio of leachate to subsurface water is based on Appendix C of the ECC Remedial Investigation report.

Acceptable Soil Concentrations based on ingestion of soil were considered, but were eliminated. For each parameter showing an Acceptable Soil Concentration in Attachment 1, the standards based on subsurface water ingestion are significantly lower than the standards based on soil ingestion. Because the site will be COVERED With a Subtitle C cap and direct contact with the soil will be prevented, the pathway of most concern is through the

#### subsurface water.

Achievement of the Acceptable Soil Concentrations shown in Attachment 1 will be verified When each of the following is met: (1) Soil vapor collected from restarts of the system show calculated soil vapor concentrations in equilibrium with the Acceptable Soil Concentrations; (3) on-site till wells show compliance with the Acceptable Subsurface Water Concentrations, also shown in Attachment 1; and (3) soil samples collected onsite show compliance with the Acceptable Soil Concentrations.

When verification has been demonstrated, operation of the soil vapor extraction system will be terminated. If the Acceptable soil Concentrations are not met within five years, U.S. EPA may require implementation of the leachate/subsurface water collection and treatment system.

#### RCRA Subtitle C Cap

The cap placed on the site will have multiple layers and will comply with the requirements of Subtitle C of the Resource Conservation and Recovery Act. The cap will prevent direct contact with contaminated soils, reduce infiltration, and enhance the soil vapor extraction system.

#### Access Restrictions

Access restrictions will consist of those specified in the 1987 ROD.

### Subsurface and Surface Water Monitoring

The purpose of the subsurface and surface water monitoring is to detect the presence of the volatile organic compounds, base neutral/acid organics, PCBs, and heavy metals specified in Attachment 1 in the subsurface and surface water during and after soil vapor extraction, and to provide information to determine the effectiveness of the soil vapor extraction program.

Once the Acceptable Soil Concentrations have been verified, and the soil vapor extraction system has been shut off, sampling of off-site till wells, on-site till wells, off-site sand and gravel wells, and surface water will be conducted for seven years on a semi-annual basis.

If, during the seven years of monitoring, cleanup levels are exceeded, construction of a ground water collection trench and the treatment of the collected ground water will occur. This action is substantively identical to the component of the 1987 remedy requiring construction of a french drain, onsite treatment of the collected ground water, and discharge pursuant to an National Pollutant Discharge Elimination System permit to Finley

Creek. This amended remedy contemplates a more flexible approach to this activity, however, in that the trench may be located in closer proximity to the contaminated area, and the collected ground water may be sent to a publicly owned treatment works, consistent with applicable law and regulations.

Table 1 is a summary comparison of the 1987 ROD and the 1989 ROD Amendment relative to the Agency's nine evaluation criteria.

### VI. STATUTORY DETRIBUTIONS

U.S. EPA has determined, and the Indiana Department of Environmental Management concurs, that the remedy selected in this ROD Amendment satisfies the statutory requirements specified in Section 121 of SARA to protect human health and the environment; attain ARARS; utilize permanent solutions and alternative treatment technologies to the maximum extent practicable, and to provide for a cost-effective response.

#### Protection of Ruman Health and the Environment

The remedy selected in this ROD Amendment will eliminate the migration of contaminants in the subsurface water and will prevent their discharge into the Unnamed Ditch and Finley Creek. This will be accomplished by removing organic chemicals from the soil through soil vapor extraction.

Some short term air and water releases may occur during the construction of the soil vapor extraction system. Engineering controls will be employed to minimize the releases, in accordance with any applicable laws and regulations.

# Attainment of Applicable, or Relevant and Appropriate Requirements

Section 121(d) of SARA requires that remedial actions meet legally applicable or relevant and appropriate requirements (ARARs) of other environmental laws. These laws may include: the Resource Conservation and Recovery Act (RCRA), the Clean Water Act (CWA), the Clean Air Act (CAA), the Toxic Substances Control Act (TSCA), the Safe Drinking Water Act (SDWA), and certain State laws which have stricter requirements than the corresponding Federal law. A "legally applicable" requirement is one which would legally apply to the response action if that action were not taken pursuant to section 104 or Section 106 of CERCLA. A "relevant and appropriate requirement" is one that, while not legally applicable to the remedial action, addresses problems or situations sufficiently similar to those encountered at the site that their use is well suited to the remedial action.

The discussion contained in the 1987 ROD pertaining to ARARS Continues to be pertinent to the amended remedy. The method for

achieving compliance with those ARARs, though, has been modified.

The following is a description of the ARARs for the amended components of the remedy and an explanation of how this amended remedial action meets those requirements:

1. RCRA Closure/Post Closure Requirements.

The amended remedy will satisfy closure and post-closure requirements of RCRA and the analogous State of Indiana requirements applicable to hazardous waste landfills.

The 1987 remedy specified a RCRA Subtitla C cap, a french drain, ground water collection and treatment, and 30 years of ground water monitoring. The amended remedy herein provides for the utilization of enhanced soil vapor extraction technology to substantially reduce the levels of contaminants remaining onsite, construction of the Subtitle C cap, and 7 years of surface and subsurface water monitoring once soil cleanup criteria have been verified. It also provides for construction of a subsurface water collection trench if the monitoring indicates contaminants are present above cleanup levels. This is, in essence, the "corrective action" which would be required if compliance monitoring disclosed the need for same under RCRA.

The Indiana Department of Environmental Management, which is authorised to administer RCRA, has determined, through its Commissioner, that utilization of soil vapor extraction to significantly reduce contamination in soil at the site warrants the contingent elimination of the french drain and reduction of the time period for post-closure ground water monitoring. The U.S. EPA hereby similarly determines that this modification complies with RCRA. The RCRA regulations applicable to closures of hazardous waste landfills are found at 40 CFR 265.110, et seq. Section 265.117 provides that post-closure monitoring must continue for 30 years, but that,

"Any time preceding closure of a hazardous waste unit,... the Regional Administrator may:

(i) Shorten the post-closure care period applicable to the hasardous waste management unit, if all disposal units have been closed, if he finds that the reduced period is sufficient to protect human health and the environment (e.g., leachate or ground-water monitoring results, characteristics of the hazardous waste, application of advanced technology, or alternative disposal, treatment, or reuse techniques indicate that the hazardous waste management unit or facility is secure);

It is the determination of U.S. EPA and the State of Indiana Department of Environmental Management that use of soil vapor

extraction, construction of the cap, and the tripartite verification of soil cleanup, is sufficient to protect human health and the environment, so as to justify shortening the compliance monitoring period to seven years from the date that soil cleanup has been verified. This determination is, in part, based on the fact that those contaminants which will not be significantly reduced by use of soil vapor extraction, are relatively insoluble and immobile, and therefore unlikely to migrate into the subsurface water. It is further based on the finding that soil vapor extraction will significantly reduce the volatile organic compounds and other contaminants which do migrate into and with ground water.

The soil vapor extraction remady selected herein is both "innovative" and "advanced". Its innovative aspect is a function of the use of injection and extraction trenches, with a cap, which produces a closed system. It is advanced in that it will utilize granular, activated carbon to remove the contaminants from the vapor.

Moreover, this amended remedy selects a backup component, implementation of a subsurface water collection and treatment procedure similar to the french drain specified in the 1987 ROD, if sample results disclose contaminants at levels above the subsurface and surface water cleanup levels during the seven year compliance monitoring period. The collected subsurface water would be discharged pursuant to an NFDES permit, as described in the 1987 ROD, sent to a publicly owned treatment works, or otherwise disposed of, in a manner which complies with applicable or relevant and appropriate laws and regulations, including the Clean Water Act.

### 2. On-site Soil and On-site Subsurface Water

As described above, the Acceptable Soil Concentrations and the Acceptable Subsurface Water Concentrations are ARARS for determining the level of cleanup on-site. In order for the soil vapor extraction system to be shut off, and additional remedial measures not be required, these ARARS will have to be met or exceeded.

### 3. Off-mite Subsurface Water and Surface Water

The Acceptable Stream Concentrations specified in Table 1 of the 1987 ROD remain the ARARs for off-site Subsurface water and Surface water. In addition, a cleanup level for PCBs has been added, which represents a 1x10-6 risk level. The remedy selected in this ROD Amendment will meet or exceed these ARARS.

#### 4. Subsurface Water Protection .

The subsurface water from underneath Enviro-Chem generally flows

to the southeast and discharges into the Unnamed Ditch. The removal of organic chemicals from the soil, and the subsequent prevention of contaminant migration are consistent with U.S. SPA's Ground Water Protection Strategy. In addition, the State's drinking water and industrial water standards would not be jeopardized thus adhering to Indiana's nondegradation policy.

# 5. On-Site Construction Activities

The on-site construction activities at Enviro-Chem may create fugitive dust. Any precautions required by state or other applicable laws will be taken during construction to minimize fugitive dust emissions.

### Cost-Effectiveness

The modified remedy selected in this ROD Amendment is as protective as, and offers greater long-term effectiveness than the 1987 ROD remedy. In the 1987 ROD, the cost of the combined remedy was estimated to be \$33.9 million. This modified remedy, for ECC alone, is estimated to cost at minimum \$4 million and at most, \$8 million. The modified remedy selected in this ROD Amendment is a cost-effective solution.

Utilization of Persanent Solutions and Alternative Treatment Tachnologies to the Maximum Extent Practicable, and Praference for Treatment as a Principal Element

If the soil vapor extraction program selected in this ROD Amendment is successful, the concentrations of organic chemicals in on-site soils and subsurface water will be permanently reduced to levels which are below those shown in Attachment 1. If the soil vapor extraction program is not successful within the required timeframe, subsurface water will be collected and treated, preventing the migration of contaminants off-site.

## VII. FUTURE ACTIONS

The anticipated Remedial Design and Remedial Action schedule is attached as Figure 2.




Figure 1

. Attachment 1

# TABLE 3-1 (Page 1 of 2) SITE-SPECIFIC ACCEPTABLE CONCENTRATIONS ENVIRONMENTAL CONSERVATION AND CHEMICAL COMPONATION (ECC) SITE

| Compounds                   | Accepte Subsurface Concentratio (up/ | Unter<br>m (1,2)<br>.) | Acceptable Stream<br>Componeration (3,4)<br>(ug/l) | Acceptable Soil Concentration (5,6) (ug/kg) |
|-----------------------------|--------------------------------------|------------------------|--|---|
| VOLATILE DREAMICS (VOCE);   |                                      |                        |  |   |
| Acetone                     | 3,500                                | RS.                    |  | 490   |
| Chlorebenzene               | 40                                   | ACLEP                  |  | 10,100                                      |
| Chloreform                  |                                      | HCL                    | 13,7   | 5,300                                       |
| 1,1-Dichlorouthene          | 0.34                                 | RB .                   |  | 5.7   |
| 1,1-91chleroethum           | 7                                    | MEL                    | 1.85   | 120   |
| Ethylbenzene                | 680                                  | HCLGP                  | 3,280  | 234,000                                     |
| Hethylene Chloride          | 4.7                                  | R.S                    | 15.7   | 20  |
| Nuthyl Ethyl Ectons         | מלו                                  | LOWA                   |  | . 75  |
| Hethyl Isobutyl Ketone      | 1.750                                | N                      |  | 5,900                                       |
| Tetrachlorgethens           | 0.47                                 | AB                     | 8.85   | 130   |
| Toluene                     | 2,000                                | NCLO                   | 3,400  | 238,000                                     |
| 1,1,1-Trichloroethane       | •                                    | MCL                    | 5,280  | 7,200                                       |
| 1, 1, 2-1-1ch Lorescharm    | 9.61                                 | 25                     | 41.8   | 22  |
| Trichloroethene             | 5                                    | ACT.                   | 90.7   | 240   |
| Total Kylenes               | 440                                  | MCLOP                  | • • •  | 195,000                                     |
| BASE MEUTRAL/ACID DECANICS: |                                      |                        |  |   |
| Bis(Z-athy(hexyl)phthslate  | 7.5                                  | 25                     | 50,000   |   |
| Di-m-Butyl Phthelate        | 3,500                                | to .                   | 154,000  |   |
| Disthyl Phthalate           | 28.000                               |                        | 52,100   |   |
| Isopharone                  | 8.5                                  | _                      | 55, 755  |   |
| <b>Haphthalene</b>          | 14,000                               |                        | 620  |   |
| Phenel                      | 1,400                                |                        | 570  | 9.800                                       |
| INORGANICS:                 | 11110                                |                        | 2,0  | 7,000                                       |
| Antimony                    | 16                                   | 25                     |  |   |
| Artenic                     |                                      | MCL                    | 0.0175   |   |
| Barium                      | 1,000                                |                        | 0.0113   |   |
| Beryllium                   |                                      |                        |  |   |
| Cardelium                   |                                      | MCL                    |  |   |
| Chrowium VI                 | 50                                   | NCL                    | 11   |   |
| Lood                        |                                      | HCL.                   | 10   |   |
| Kanganese                   | 7,000                                | U                      |  |   |
| Hickel                      | ·                                    | LDUMA                  | 190  |   |
| Silver                      | 50                                   | NCL.                   | ****   |   |
| Tin                         | 21,000                               |                        |  |   |
| Vanadius                    | 345                                  |                        |  |   |
| Zins                        | 7.000                                |                        | 47   |   |
| Eyenide                     | 154                                  |                        | 5.2  |   |
| PESTICIDES/PCS+1            | 100                                  |                        | <b>/-</b> 1  |   |
| PCBs                        | 0.0045                               | XB (7)                 | 0.000079 (7,8)                                     |   |

| Post-It* Fax Note | 76 | 71       | Date | 10/13    | pages 12 | 6        |
|-------------------|----|----------|------|----------|----------|----------|
| TO NWB            |    |          | From | M.O      | OWIAK    |          |
| Co/Dept.          |    | $\sum C$ | 3    | <u> </u> |          |          |
| Phone #           | 10 | 13       | 10   |          |          |          |
| Fax #             |    |          | Fax# | 202      | 166 887  | <u> </u> |

Attachment 1

SITE-SPECIFIC ACCEPTABLE CONCENTRATIONS
ENVIRONMENTAL CONSERVATION AND CHEMICAL CORPORATION (ECC SITE)

#### NOTES:

- (1) RB = Risk-based standard. U.S. EPA, Draft RCRA Facility Investigation Guidance, 1987.
  - MCL = Drinking water Maximum Contaminant Level. 40 CFR
  - MCLGP = Drinking water MCL goal, proposed. U. S. SFA Superfund Public Health Evaluation Manual, update of November 16, 1987.
  - LDWHA = Lifetime drinking water health advisory. U.S. RPA, superfund Public Health Evaluation Manual, update of November 16, 1987.
- In the event that higher concentrations than those set forth for any parameter in this column are present in the upgradient subsurface water in the till and/or sand and gravel according to the procedure specified below, then those higher upgradient subsurface water concentrations and not the values set forth in this table shall constitute the Acceptable Subsurface Water Concentrations within the meaning of this Exhibit A and the Consent Decree. Those upgradient subsurface water concentrations are referred to in this Exhibit A as "Applicable Subsurface Water Background Concentrations. Twelve subsurface water samples will be taken from existing or new well locations, approved by EPA, over at least a 12 month period in areas upgradient of the site. The exact procedure, location of wells, and schedule for collecting and analyzing the samples will be approved by EPA, after consultation with the State, prior to its implementation. Subsurface samples for inorganics and PCB analysis will be filtered. For each parameter, the analytical results from the 12 samples will be analyzed using standard statistical procedures. The mean and standard deviation will be calculated, and all nondetects will be assigned a value equal to 1/2 the EPA-approved quantification limit. For purposes of this Document, "Applicable Subsurface Water Background Concentrations" is defined as two (2) standard deviations above the calculated mean of these 12 samples.
- (3) Stream Criteria, from Table 1 of the Record of Decision for the site, September 25, 1987.
- (4) In the event that higher concentrations than those set forth for any parameter in this column are present in the upstream surface vater, then those higher upstream concentrations and not the values set forth in this table shall constitute the Acceptable Stream Concentrations within the meaning of this Exhibit A and the Consent Decree. Those higher upstream surface water concentrations are referred to in this Exhibit A as

FAX NO. 4127881316 FAX NO. 3174690708 P. 02 **P. 16** 

SEP-14-92 MUN 14:35

AWD LECHNOLUGIES INDY

#### Attachment 1

"Applicable Surface Water Background Concentrations." Twelve surface water samples will be taken from Unnamed Ditch upstream of the site over at least a 12 month period. The exact procedure, location of samples, and schedule for collecting and analyzing the samples will be approved by EPA, after consultation with the State, prior to its implementation. For each parameter, the analytical results from the 12 samples will be analyzed using standard statistical procedures. The mean and standard deviation will be calculated, and all non-detects will be assigned a value equal to 1/2 the EPA-approved quantification limit. For purposes of this Document, "Applicable Surface Water Background Concentrations" is defined as two (2) standard deviations above the calculated mean of these 12 samples.

- (5) Acceptable Soil Concentration is based on ingestion of subsurface water at the site boundary, assuming a dilution of leachate to subsurface water of 1:196 (Appendix B).
- (5) The Acceptable Soil Concentrations, within the meaning of this Exhibit A and the Consent Decree, will be achieved when the arithmetic average of the 20 soil sample results for each parameter, assigning all non-detect results a value of one-half the detection limit, do not exceed the values set forth in this table by more than 25 percent.
- (7) So long as the EPA-approved quantification limit for PCBs in water is above the acceptable subsurface water and stream concentrations for PCBs, compliance with the Acceptable Subsurface and Stream Concentrations for PCBs will be determined as follows: all subsurface and surface water sample results for PCBs must be below the EPA-approved quantification limit for PCBs (at the time compliance is determined).
- (8) Modified from Superfund Public Health Evaluation Manual, October, 1986, EPA 4/540/1-86/060, OSWER Directive 9285.4-1.

FAX NO. 4127881316

P. 03 P. 17

SEP-14-92 MON 14:38

AWD TECHNOLOGIES INDY FAK NO. 3174690708

|  | 1987 RENEDY   | MODIFIED REMEDY   |
|--|---|---|
| Protection of human health and the environment     | Surface water pro-<br>tected by ground<br>water collection  | Surface water pro-<br>tected by soil<br>vapor extraction  |
| Compliance with ARARS                              | Compliance with off-<br>site ARARs (Accep-<br>table Stream<br>Criteria)   | Compliance with off-site ARARs, (Acceptable Stream Criteria), on-site ARARs (Acceptable Soil Concentrations and Acceptable Subsurface Water Concentrations) |
| Long-term<br>Effectiveness                         | Lose certain, due to<br>slower removal of<br>contaminants, and<br>the need for long-<br>term maintenance of<br>the treatment system | Paster removal of contaminants, and less time required for long-term maintenance  |
| Reduction in<br>Toxicity, Mo-<br>bility and Volume | Slow reduction in<br>volume of contan-<br>inants from ground<br>water collection  | Paster reduction in volume of con-<br>taminants from soil vapor extraction  |
| Short-term<br>Effectiveness                        | Little site distur-<br>bance; little chance<br>of releases during<br>construction   | Possibility of air and water releases during construction; these will be minimized through engineering controls   |
| Implementability                                   | Simple construction;<br>long-term operation<br>and maintenance re-<br>quired  | More complex con-<br>struction; oper-<br>ation and mainte-<br>nance time reduced  |
| Cost   | \$3 million   | \$4 to \$8 Million  |
| State Acceptance                                   | rull acceptance   | Full acceptance   |
| Community Acceptance                               | Full acceptance   | Anticipate ac-<br>ceptance  |

P. 18

-SEP-14-92 MON 14:36

AND TECHNOLOGIES INDY FAX NO. 3174690708




Figure 2

FAX NO. 4127881316 FAX NO. 31/4690/08

P. 05 P. 19

# Declaration for the Record of Decision Amendment

#### Site Name and Location

Environmental Conservation and Chemical Corporation, Zionsville, Indiana

#### Statement of Basis and Purpose

This decision document, together with a Record of Decision dated September 25, 1987, represents the selected remedial action for the Environmental Conservation and Chemical Corporation site developed in accordance with the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA), as amended by the Superfund Amendments and Reauthorisation Act of 1986 (SARA), and to the extent practicable, the National Oil and Hazardous Substances Pollution Contingency Plan (NCP).

This decision is based on the contents of the administrative record for the Environmental Conservation and Chemical Corporation site. The attached index identifies the items which comprise the administrative record upon which the decision to amend the 1987 Record of Decision, and the selection of the modified remedial action is based.

The State of Indiana concurs in the remedy selected by U.S. EFA for the Environmental Conservation and Chemical Corporation site.

#### Description of the Remedy

The primary reason for amending the 1987 Record of Decision is to reflect the decision to implement separate, complementary remedies for the Environmental Conservation and Chemical Corporation and Northside Sanitary Landfill sites, instead of the one combined remedy selected in the 1987 Record of Decision, and secondarily, to modify the selected remedy.

For the Environmental Conservation and Chemical Corporation site, the major components of the remedial action, as modified, include:

- Soil vapor extraction, concentration and destruction
- RCRA Subtitle C cap
- Access restrictions
- Subsurface and surface water monitoring
- Contingent subsurface water collection and treatment

٠.

FAX NO. 4127881316 FAX NO. 3174690708

P. 06

#### <u>Declaration</u>

The selected remedy, as modified herein, is protective of human health and the environment, attains Federal and State requirements that are applicable or relevant and appropriate to this remedial action, and is cost-effective.

This remedy satisfies the statutory preference for remedies that employ treatment that reduce toxicity, mobility or volume as a principal element and utilise permanent solutions and alternative treatment technologies to the maximum extent practicable.

Because this remedy will result in hazardous substances remaining on-site, pursuant to Section 121(c) of CERCIA, a review will be conducted at the site within five years after commencement of the remedial action and at least every five years thereafter to ensure that the remedy continues to provide adequate protection of human health and the environment.

Date

Valdes V. Adamkus Regional Administrator Region V